201-15005B

IUCLID

Data Set

Existing Chemical

CAS No.

EINECS Name

EC No.

TSCA Name

Molecular Formula

: ID: 74-86-2

: 74-86-2

: acetylene

: 200-816-9

: Ethyne : C2H2

Producer related part

Company Creation date : American Chemistry Council, Acetylene Panel

: 15.08.2003

Substance related part

Company **Creation date** : American Chemistry Council, Acetylene Panel

: 15.08.2003

Status

Memo

Printing date

Revision date Date of last update : 09.12.2003 : 09.12.2003

: 09.12.2003

Number of pages

: 31

Chapter (profile) Reliability (profile) : Chapter: 1, 2, 3, 4, 5, 6, 7, 8, 10 : Reliability: without reliability, 1, 2, 3, 4

Flags (profile)

: Flags: without flag, confidential, non confidential, WGK (DE), TA-Luft (DE), Material Safety Dataset, Risk Assessment, Directive 67/548/EEC, SIDS

1. General Information

ld 74-86-2 **Date** 21.10.2003

1.0.1 APPLICANT AND COMPANY INFORMATION

1.0.2 LOCATION OF PRODUCTION SITE, IMPORTER OR FORMULATOR

1.0.3 IDENTITY OF RECIPIENTS

1.0.4 DETAILS ON CATEGORY/TEMPLATE

1.1.0 SUBSTANCE IDENTIFICATION

IUPAC Name : ethyne IUPAC Name : ethyne
Smiles Code : C#C
Molecular formula : C2H2
Molecular weight : 26.04
Petrol class :

Petrol class

Reliability : (1) valid without restriction

15.08.2003

1.1.1 GENERAL SUBSTANCE INFORMATION

: typical for marketed substance

Purity type
Substance type
Physical status
: typical ic.
: organic
: gaseous
: >=

Colour : colorless, clear

Odour : faint ether or garlic like odor

15.08.2003 (20)

1.1.2 SPECTRA

1.2 SYNONYMS AND TRADENAMES

1.3 **IMPURITIES**

1.4 **ADDITIVES**

1.5 **TOTAL QUANTITY**

1.6.1 LABELLING

1. General Information

ld 74-86-2 **Date** 21.10.2003

1.6.2 CLASSIFICATION

1.6.3 PACKAGING

1.7 USE PATTERN

Type of use : industrial

Category : Basic industry: basic chemicals

15.08.2003

1.7.1 DETAILED USE PATTERN

Remark : Used as a chemical intermediate in the manufacture of other chemicals

and in welding.

15.08.2003

1.7.2 METHODS OF MANUFACTURE

1.8 REGULATORY MEASURES

1.8.1 OCCUPATIONAL EXPOSURE LIMIT VALUES

1.8.2 ACCEPTABLE RESIDUES LEVELS

1.8.3 WATER POLLUTION

1.8.4 MAJOR ACCIDENT HAZARDS

1.8.5 AIR POLLUTION

1.8.6 LISTINGS E.G. CHEMICAL INVENTORIES

1.9.1 DEGRADATION/TRANSFORMATION PRODUCTS

1.9.2 COMPONENTS

1.10 SOURCE OF EXPOSURE

1. General Information

- 1.11 ADDITIONAL REMARKS
- 1.12 LAST LITERATURE SEARCH
- 1.13 REVIEWS

2. Physico-Chemical Data

Id 74-86-2 Date 21.10.2003

2.1 **MELTING POINT**

Value = -80.8 °C

Sublimation

Method : other Year

GLP : no

Test substance : as prescribed by 1.1 - 1.4

Reliability (2) valid with restrictions

Peer reviewed data that came from a reliable reference textbook.

Flag : Critical study for SIDS endpoint

15.08.2003 (17)

2.2 **BOILING POINT**

= -84 °C at 1016 hPa Value

Decomposition

Method : other Year **GLP**

Test substance as prescribed by 1.1 - 1.4

Remark Sublimes at boiling point. Verschueren, K. Handbook of Environmental

Data of Organic Chemicals. 2nd ed. New York, NY: Van Nostrand Reinhold

Co., 1983. 154.

Reliability (2) valid with restrictions

Peer reviewed data that came from a reliable reference textbook.

Critical study for SIDS endpoint Flag

15.08.2003 (17)

2.3 DENSITY

Type : relative density Value = .6208 at -82 °C

Method : other

Year

GLP :

Test substance as prescribed by 1.1 - 1.4

Reliability (2) valid with restrictions

Peer reviewed data that came from a reliable reference textbook.

15.08.2003 (17)

2.3.1 GRANULOMETRY

VAPOR PRESSURE

= 6969.2 hPa at 25 °C Value

Decomposition

Method other (calculated)

Year

GLP : no

2. Physico-Chemical Data

ld 74-86-2 **Date** 21.10.2003

Test substance: as prescribed by 1.1 - 1.4

Remark: Vapor pressure from experimentally derived coefficients.

Result : Vapor pressure = 40 ATM @ 16.8 DEG C.

Sax, N.I. Dangerous Properties of Industrial Materials. 6th Ed. New York,

NY: Van Nostrand Reinhold, 1984. 107.

Reliability : (2) valid with restrictions

Peer reviewed data that came from a reliable reference textbook.

Flag : Critical study for SIDS endpoint

15.08.2003 (3)

2.5 PARTITION COEFFICIENT

Partition coefficient : octanol-water Log pow : = 0.37 at 20 °C

pH value : = 7

Method : other (calculated)

Year

GLP : no

Test substance: as prescribed by 1.1 - 1.4

Reliability : (2) valid with restrictions

Data calculated by a reliable source using a recognized document

estimation method.

Flag : Critical study for SIDS endpoint

15.08.2003 (13)

2.6.1 SOLUBILITY IN DIFFERENT MEDIA

Solubility in : Water

Value : = 1230 mg/l at 20 $^{\circ}$ C and 1013 hPa

pH value : = 7

Reliability : (2) valid with restrictions

Data came from a reliable reference textbook.

Flag : Critical study for SIDS endpoint

25.11.2003 (12)

Solubility in : Water

Value : = 1200 mg/l at 25 °C

pH value : = 7

Reliability : (2) valid with restrictions

Data are from a secondary source. The primary source is a reliable

reference textbook that was not consulted.

15.08.2003 (21)

2.6.2 SURFACE TENSION

2.7 FLASH POINT

2.8 AUTO FLAMMABILITY

2. Physico-Chemical Data

Id 74-86-2 **Date** 21.10.2003

FLAMMABILITY 2.9

Result : extremely flammable

Method : other

Year

GLP : no

Test substance : rio : as prescribed by 1.1 - 1.4

: Flammable Limits: Upper: 100% by vol.; Lower 2.5% by vol.: (2) valid with restrictions Result

Reliability

15.08.2003 (10)

EXPLOSIVE PROPERTIES

2.11 OXIDIZING PROPERTIES

2.12 DISSOCIATION CONSTANT

2.13 VISCOSITY

2.14 ADDITIONAL REMARKS

3. Environmental Fate and Pathways

ld 74-86-2 **Date** 21.10.2003

3.1.1 PHOTODEGRADATION

Type : air
Light source : Sun light
Light spectrum : nm

Relative intensity : based on intensity of sunlight

INDIRECT PHOTOLYSIS

Sensitizer : OH Conc. of sensitizer :

Rate constant : = .00000000000815 cm³/(molecule*sec)

Degradation : = 50 % after 13.1 day(s)

Deg. product

Method : other (calculated)

Year : 2003 **GLP** : no

Test substance: as prescribed by 1.1 - 1.4

Remark: Measured inputs to the program were melting point (-80.8)

degrees C), boiling point (-84 degrees C), vapor pressure

(5240 mm Hg) and water solubility (1,200 mg/l).

Reliability : (2) valid with restrictions

Data were estimated using a model.

Flag : Critical study for SIDS endpoint

15.08.2003 (2)(5)

3.1.2 STABILITY IN WATER

Deg. product

Method : other (calculated)

Year : 2003 **GLP** : No

Test substance: as prescribed by 1.1 - 1.4

Remark: Measured inputs to the program were melting point (-80.8 degrees C),

boiling point (-84 degrees C), vapor pressure (5240 mm Hg) and water

solubility (1,200 mg/l).

Result : EPIWIN Hydrowin cannot calculate hydrolysis rate constant for molecular

structures of the acetylene type. Hydrolysis of acetylene in water is likely to be an unimportant pathway, because acetylene does not possess a functional group known to be susceptible to hydrolysis at neutral ambient conditions. Also, despite acetylene's measurable solubility in water, acetylene has a pronounced tendency to quickly volatilize from water to the atmosphere, based on its high vapor pressure and existence as a gas at

ambient temperature.

Reliability : (3) invalid

15.08.2003 (9)

3.1.3 STABILITY IN SOIL

3.2.1 MONITORING DATA

3.2.2 FIELD STUDIES

3. Environmental Fate and Pathways

ld 74-86-2 **Date** 21.10.2003

3.3.1 TRANSPORT BETWEEN ENVIRONMENTAL COMPARTMENTS

Type : fugacity model level III

 Media
 : soil - air

 Air
 : 99.9 %

 Water
 : 0.104 %

 Biota
 : 0.000177 %

 Soil
 : 0.0101 %

 Method
 : Other

 Year
 : 2003

Remark: Measured inputs to the program were melting point (-80.8 degrees C),

boiling point (-84 degrees C), vapor pressure (5240 mm Hg) and water solubility (1,200 mg/l). The emission rate values of 1000 kg/hr to air, and 0

kg/hr to water, sediment and and soil were inputted.

Result: Estimated half-lives in various media are: air = 298 hours, water = 360

hours, soil = 360 hours and sediment = 1440 hours. The soil/sediment constant Koc = 14.3, as estimated by the EPIWIN PcKoc Program (v1.66). The Henry's Law Constant calculated by EPIWIN Henry (v3.10) = 2.40 E-

002 atm-m3/mole.

Reliability : (2) valid with restrictions

Data were calculated using a well-recognized computer estimation

program.

Flag : Critical study for SIDS endpoint

15.08.2003 (8)

3.3.2 DISTRIBUTION

3.4 MODE OF DEGRADATION IN ACTUAL USE

3.5 BIODEGRADATION

Deg. product

Method : other (calculated)

Year : 2003 GLP : No

Test substance : as prescribed by 1.1 - 1.4

Remark: Measured inputs to the program were melting point (-80.8 degrees C),

boiling point (-84 degrees C), vapor pressure (5240 mm Hg) and water

solubility (1,200 mg/l).

Result : EPIWIN BIOWIN (v4.00) predicts ready biodegradability using both

nonlinear and linear methods

Reliability : (2) valid with restrictions

Data were obtained by modeling.

15.08.2003 (6)

3.6 BOD5, COD OR BOD5/COD RATIO

3.7 BIOACCUMULATION

3. Environmental Fate and Pathways

ld 74-86-2 **Date** 21.10.2003

3.8 ADDITIONAL REMARKS

ld 74-86-2 4. Ecotoxicity Date 21.10.2003

4.1 ACUTE/PROLONGED TOXICITY TO FISH

Type other: estimation

Species other Exposure period 96 hour(s) Unit mg/l

LC50 = 496.148 calculated

Limit test

Analytical monitoring

Method other: calculated

Year 2003 **GLP** :

Test substance : as prescribed by 1.1 - 1.4

Remark Measured inputs to the program were melting point (-80.8 degrees C),

boiling point (-84 degrees C), vapor pressure (5240 mm Hg) and water

solubility (1,200 mg/l).

This is a supporting study for the SIDS endpoint.

Reliability (2) valid with restrictions

Data were calculated using a computer program.

05.09.2003 (7)

Type other: no data **Species** Lepomis sp. Exposure period 1 hour(s)

Unit

Method other

Year

GLP no data

Test substance as prescribed by 1.1 - 1.4

Remark : Exposure of sunfish to 1000 ppm acetylene (at 18 degrees C) did not result

> in death. No other information was provided. This is a supporting study for the SIDS endpoint.

Source The primary source of the data was not cited in the OHM/TADS data file.

Reliability (4) not assignable

There are not enough details to assign a reliability rating.

05.09.2003 (18)

other: no data Type **Species** other: minnow Exposure period 1 hour(s)

Unit

Source

Method other Year

GLP

Test substance as prescribed by 1.1 - 1.4

Remark Exposure of minnows (no species indicated) to 17 ppm acetylene in well-

oxygenated water had no effect.

This is a supporting study for the SIDS endpoint. The primary source of the data was not cited in the OHM/TADS data file.

Reliability (4) not assignable

There are not enough details to assign a reliability rating.

05.09.2003 (18)

Type other: no data Species other: trout fingerlings

Exposure period 33 hour(s)

11/31

4. Ecotoxicity ld 74-86-2

Pate 21.10.2003

Unit : mg/l Method : other

Year

GLP : no data

Test substance: as prescribed by 1.1 - 1.4

Remark : Exposure of trout fingerlings to 200 ppm acetylene at 10-14 degrees C

resulted in death to an unlisted number of fish.

This is a supporting study for the SIDS endpoint.

Source: The primary source of the data was not cited in the OHM/TADS data file.

Reliability : (4) not assignable

There are not enough details to assign a reliability rating.

05.09.2003 (18)

Type : other: no data
Species : Cyprinus auratus

Exposure period

Unit : mg/l Method : other Year :

GLP : no data

Test substance: as prescribed by 1.1 - 1.4

Remark: Exposure of goldfish to 400 ppm acetylene for 24 to 48 hours resulted in

death to an unlisted number of fish.

This is a supporting study for the SIDS endpoint.

Source: The primary source of the data was not cited in the OHM/TADS data file.

Reliability : (4) not assignable

There are not enough details to assign a reliability rating.

05.09.2003 (18)

Type : other

Species: other:fingerling chinook salmon

Exposure period : 72 hour(s)

Unit

Method : other

Year

GLP : no data

Test substance : as prescribed by 1.1 - 1.4

Remark: The "critical level" at 72 hours for fingerling chinook salmon in brackish

water was 3500 ppm.

This is a supporting study for the SIDS endpoint.

Source: The primary source of the data was not cited in the OHM/TADS data file.

Reliability : (4) not assignable

There are not enough details to assign a reliability rating.

05.09.2003 (18)

Type : other: no data

Species: other: young rainbow trout

Exposure period : 72 hour(s)

Unit

Method : other Year :

GLP : no data

Test substance : as prescribed by 1.1 - 1.4

Remark : The "critical level" at 72 hours for young rainbow trout in fresh water was

3000 - 5000 ppm.

This is a supporting study for the SIDS endpoint.

Source: The primary source of the data was not cited in the OHM/TADS data file.

Reliability : (4) not assignable

12/31

4. Ecotoxicity ld 74-86-2

Pate 21.10.2003

There are not enough details to assign a reliability rating.

05.09.2003 (18)

4.2 ACUTE TOXICITY TO AQUATIC INVERTEBRATES

Type : other: calculated

Species: Daphnia magna (Crustacea)

Exposure period : 48 hour(s)
Unit : mg/l

EC50 : = 479.304 calculated

Analytical monitoring : no

Method : other: calculated

Year : 2003 GLP : no

Test substance: as prescribed by 1.1 - 1.4

Remark: Measured inputs to the program were melting point (-80.8 degrees C),

boiling point (-84 degrees C), vapor pressure (5240 mm Hg) and water

solubility (1,200 mg/l).

Reliability : (2) valid with restrictions

Data were calculated using a computer program.

Flag : Critical study for SIDS endpoint

15.08.2003 (7)

4.3 TOXICITY TO AQUATIC PLANTS E.G. ALGAE

Species : other algae: green algae

Endpoint : growth rate
Exposure period : 96 hour(s)
Unit : mg/l

EC50 : = 274.86 calculated

Remark: Measured inputs to the program were melting point (-80.8 degrees C),

boiling point (-84 degrees C), vapor pressure (5240 mm Hg) and water

solubility (1,200 mg/l).

Reliability : (2) valid with restrictions

Data were e stimated by a computer program.

Flag : Critical study for SIDS endpoint

15.08.2003 (7)

4.4 TOXICITY TO MICROORGANISMS E.G. BACTERIA

4.5.1 CHRONIC TOXICITY TO FISH

4.5.2 CHRONIC TOXICITY TO AQUATIC INVERTEBRATES

4.6.1 TOXICITY TO SEDIMENT DWELLING ORGANISMS

4.6.2 TOXICITY TO TERRESTRIAL PLANTS

4. Ecotoxicity

163	TOYICITY TO SOIL	DWFI LING ORGANISMS
4.0.3	TOXICH FIO SOIL	. DWELLING URGANISIVIS

- 4.6.4 TOX. TO OTHER NON MAMM. TERR. SPECIES
- 4.7 BIOLOGICAL EFFECTS MONITORING
- 4.8 BIOTRANSFORMATION AND KINETICS
- 4.9 ADDITIONAL REMARKS

5.0 TOXICOKINETICS, METABOLISM AND DISTRIBUTION

5.1.1 ACUTE ORAL TOXICITY

5.1.2 ACUTE INHALATION TOXICITY

Type : other

Value :

Species : human

Strain : Sex : Number of animals :

Vehicle

Doses : 100,000, 150,000, 200,000, 250,000, 300,000, 330,000 and 350,000 ppm

Exposure time

Method: otherYear: 1925GLP: no

Test substance: as prescribed by 1.1 - 1.4

Remark: It is evident from this study that the LD50 value in humans is greater than

10% (100,000 ppm).

Result : Inhalation of 10% caused feelings of mild intoxication with parethesia, and

had a slight effect on reaction time. Fifteen percent caused distinct intoxication with talkativeness, sleepiness and inability to walk a straight line, but did not include symptoms of marked intoxication (even after an hour's inhalation). Marked intoxication was evident after inhalation of 20% for 4 minutes. Slight uncoordination of head movements was noticed after 20% had been inhaled for 18 minutes. Twenty five percent acetylene caused similar but more marked symptoms. An effect on writing, typewriting, simple reaction time or memory was not observed after inhalation of less than 20 - 25%. General uncoordination and aggressive behavior were noted after inhalation of 30% acetylene for 13 minutes. Inhalation of 33% or 35% caused unconsciousness within 7 and 5 minutes, respectively. Inhalation of 50% acetylene produced feelings of intense intoxication within 35 seconds and an unbearable feeling of suffocation in

70 seconds (after which the experiment was stopped).

Test condition: Humans (number and sex were not listed) were administered acetylene (10

- 50 %) from a Douglas bag in the sitting position. No re-breathing was allowed. The acetylene was obtained from the Bon-Accord Acetylene Gas Company, and was prepared from calcium carbide and purified by passing through a lime-tower. Clinical signs were monitored and the concentration that produced unconsciousness (and exposure time) was listed. The effects of a cetylene inhalation on memory, reflex times and muscular

movement also were assessed.

Reliability : (2) valid with restrictions

The number of humans tested was not listed. Although the purity of the material was not listed, it is assumed that it is offairly high purity since it

was purified before use.

Flag : Critical study for SIDS endpoint

05.09.2003 (4)

Type : Other Value : Species : Rat Strain :

15/31

Id 74-86-2 5. Toxicity Date 21.10.2003

Sex Number of animals

Vehicle

Doses 780,000 and 900,000 ppm

Exposure time

Test condition

Method : other Year 1925 : **GLP** : no

Test substance as prescribed by 1.1 - 1.4

Result : A concentration of 78% acetylene (780,000 ppm) produced anesthesia in

15 minutes. Acetylene did not cause m arked excitement before

anesthesia.

A concentration of 90% acetylene (900,000 ppm) caused respiratory failure in approximately 2 hours. It assumed that this concentration was lethal. Acetylene and other gases were tested for inhalation toxicity in a single

strain of white rats of uniform weight (number and sex of animals and

details about exposure were not provided).

Reliability (4) not assignable

Not enough details are present to assign a reliability rating.

05.09.2003 (19)

other Type

Value

Species dog Strain Sex **Number of animals**

Vehicle Doses **Exposure time**

Method : other Year 1925 : **GLP** no

Test substance as prescribed by 1.1 - 1.4

Remark Inhalation of 50 dogs to 850,000 ppm increased respiratory volume and

frequency and induced anesthesia, with rapid recovery. Therefore, the

LD50 value in this study is greater than 850,000 ppm.

(4) not assignable Reliability

There are not enough data to assign a reliability rating. The original

reference was not consulted.

05.09.2003 (14)

5.1.3 ACUTE DERMAL TOXICITY

5.1.4 ACUTE TOXICITY, OTHER ROUTES

5.2.1 **SKIN IRRITATION**

5.2.2 EYE IRRITATION

5.3 SENSITIZATION

5.4 REPEATED DOSE TOXICITY

Type :
Species :
Sex :
Strain :
Route of admin. :
Exposure period :
Frequency of treatm. :
Post exposure period :

Doses : 250,000, 500,000 and 800,000 ppm

Control group

NOAEL : = 800000 ppm

Method : other Year : 1933 GLP : no

Test substance: as prescribed by 1.1 - 1.4

Remark: This is a supporting study for the SIDS endpoint.

Since capillary hyperemia was not observed in rats exposed to higher concentrations of acetylene, it does not appear to be test-material related.

Result : The numbers of animals that died spontaneously are reported in the

following table:

Animal	Conc.	Daily	Number	Total	Deaths
	(%)	Exposure	Of Days	Exposure	
		Time	Exposed	Time	
		(hours)		(hours)	
Rat	25	1	7-93	7-93	6/16
Rat	50	2	1-8	2-16	9/10
Guinea Pig	50	2	1-9	2-18	7/7
Mouse	50	2	1-6	2-12	5/5
Rat	80	1/2	2-36	1-18	36/47
Rat	80	1	14	14	0/8
Guinea Pig	80	1	10	10	0/6
Rabbit	80	1	6-10	6-10	3/4
Dog	80	1	12	12	1/2

At the lower concentrations (concentrations were not stated) the animals appeared only slightly sleepy. At higher concentrations (70-80%), the majority of animals fell asleep after 15-20 minutes. In general, these animals were not in deep narcosis. The rats, rabbits, guinea pigs and dogs generally recovered from narcosis in a short time. However, the mice did not survive treatment. Some of the animals died spontaneously. Pneumonia was observed in most of these cases. Since pneumonia also was observed in control animals exposed only to air, it did not appear to be related to treatment. In treated animals that survived to termination, the authors found no evidence of cellular injury to the parenchymatous cells of the heart, lungs, liver, kidneys, or spleen. However, capillary hyperemia was observed in the liver, kidneys and spleen of some rats exposed to 250,000 ppm (the number was not stated). This effect was observed until at least the second day after the last exposure to the gas but was not evident in animals killed later (up to 5 days after the last exposure).

Test condition

: Rats, mice, guinea pigs, rabbits, and dogs were exposed to acetylene in oxygen according to the scheme presented in the following table:

Animal	No. Tested/	Conc.	Daily	Number	Total
	Deaths/	(%)	Exposure	of Days	Exposure
	Terminated		Time	Exposed	Time
			(hours)		(hours)
Rat	16/6/12	25	1	7-93	7-93
Rat	10/9/1	50	2	1-8	2-16
Guinea Pig	7/7/0	50	2	1-9	2-18
Mouse	5/5/0	50	2	1-6	2-12
Rat	47/36/11	80	1/2	2-36	1-18
Rat	8/0/8	80	1	14	14
Guinea Pig	6/0/6	80	1	10	10
Rabbit	4/3/1	80	1	6-10	6-10
Dog	2/1/2	80	1	12	12

Thirty animals also served as controls. The number of controls for each species was not listed.

The animals were placed in glass cages that were air tight, and on one side the gassing apparatus was placed to introduce the gas, and on the other side of the cage an equal amount of air was exhausted out. This setup enabled the animals to move about freely without changes in air pressure and have the right amount of oxygen. The stream of acetylene/oxygen introduced amounted to 5 liters per minute, so that carbon dioxide buildup was ruled out for practical purposes.

As a rule, exposures were conducted daily. During the experiment, most of the animals (numbers were not stated) were weighed after various intervals. In some experiments, blood samples were taken at regular intervals from controls (numbers of animals were not stated).

Animals that survived to study termination were killed either right after the experiment or later by striking them on the head. A series of 30 controls also were killed by head strike. Three control animals showed signs of congestion from this method of killing. Most of the animals were killed and examined several hours after the last experiment. A portion were killed up to 5 or 14 days after the last exposure (individual numbers were not listed). Animals that died spontaneously the first 1-3 days after the last exposure also were examined. All animals were dissected and the organs (heart, lung, liver, kidney and spleen) were fixed in formalin or Zenker solution according to standard procedure, embedded in paraffin glycogenstain in celloiden and examined microscopically. In addition, frozen tissue slices were made and stained.

Conclusion

The authors concluded that acetylene did not cause any sort of histologically detectable damage to parenchymatous cells at the concentrations tested.

Reliability : (2) valid with restrictions

The study was not performed according to current standards.

11.09.2003 (11)

Type : Sub-chronic

Species: ratSex: maleStrain: other: albinoRoute of admin.: inhalationExposure period: 6 hours per day

Frequency of treatm. : 5 days/week for 6 months

Post exposure period

Doses : 28,700 ppm

Control group : yes, concurrent no treatment

NOAEL : < 28700 ppm

 Method
 : other

 Year
 : 1957

 GLP
 : no

 Test substance
 : other TS

Remark: This is a supporting study for the SIDS endpoint.

An acute study performed before this study showed that inhalation of

42,000 ppm for 6 hours did not cause lethality.

Result : Chamber concentration: The concentration of material in the atmosphere of

control animals was 2000 ppm. This was subtracted from the concentration analyzed in the atmosphere of exposed animals (30,700 ppm), to obtain a

corrected exposure concentration of 28,700 ppm.

Signs of toxicity during exposure: On the first day of exposure, slight ataxia was noted within 7 minutes of exposure. After one half hour, most of the rats were lying on the chamber floor, in an early plane of anesthesia. A peculiar "pecking" motion of the head was exhibited throughout the first exposure. During remaining exposures, rats were observed to be in one position, lying either on the abdomen or on the side, with gross tremors of the head and extremities. The rats appeared to be unable to maintain balance. All animals recovered rapidly after exposures were terminated.

Signs of toxicity observed following exposure: Animals were depressed after exposure, and their fur was wet, discolored and ruffled. Rats were "unthrifty" after about 2 months on study. Eight (40%) of the rats died. Times of death were listed as 21, 34 (2 deaths), 46, 74, 95, 102 and 103 days. Two of the controls died. Over the course of the study, weight gain was slightly retarded in exposed rats.

Gross pathology of animals that died was limited to the lungs, which appeared dark red. The lungs remained distended when the thorax was opened, but no edema fluid was found. On palpation, the lungs had a firm consistency. A purulent empyema was observed in one rat.

In exposed rats that survived to termination, the lungs also were discolored and remained distended. Discoloration ranged from speckled red areas to a homogeneous, dark red, hemorrhagic appearance. Cut sections of lungs were a homogeneous, dark red color and either edema fluid or blood could be expressed from them. Lungs from 3 of the 12 surviving animals had cysts which contained a "cheesy material". The remaining organs appeared to be within normal limits. Microscopic pathology of the lungs showed definite pulmonary irritation.

Test condition

Animals: A group of 20 male albino rats (avg. weight 135 g) were exposed to an average concentration of 28,700 ppm methylacetylene for 6 hours/day, 5 days/week for 6 months. An equal number of rats was housed in the same laboratory to serve as controls. The laboratory temperature was 25 +/-1 degrees C.

Exposure: Exposures were performed in 500 liter, stainless steel chambers with a water-sealed lid. The inlet was equipped with a suitable device to inject methylacetylene vapor, and the outlet was equipped with an orifice flowmeter, control valve and exhaust pump. Methylacetylene vapor was injected into the inlet at a fixed rate of flow from a large steel cylinder. A constant rate of flow was maintained during exposure with a reducing pressure valve and an orifice flowmeter, which was connected to a water manometer. The flow was constantly monitored. Methylacetylene was mixed with room air, which was drawn into the exposure chamber.

Test conduct: Animals were observed for signs of toxicity during and after

exposure (specific times were not listed). Animals were observed at least daily for mortality. Animals were weighed on days 0, 13, 24, 31, 38, 45, 60, 64, 71, 76, 85, 95, 102, 109, 120, 127, 137, 141, 146, 158, 165, 173, 179 and at termination (date was not stated). Gross pathologies of animals that died were performed as soon as possible after death. Gross pathologies of animals that survived the course of treatment were performed upon termination. Sections of lung, liver, kidney, heart, spleen and GI tract were examined microscopically.

Concentration of Test material: The concentration of material in the chamber was determined by drawing a known volume of the chamber atmosphere (measured with a wet-test meter) through 6 bubblers (in series) containing methanol. Samples were not drawn until the chamber concentration had equilibrated. The concentration of test material in each bubbler was determined separately. If an appreciable mount of material was found in the last bubbler, the samples were drawn at a slower rate. Blank samples from chambers containing control animals were run to determine the contribution of animal metabolites.

Solution from each bubbler was placed into a 250 ml volumetric flask, containing 50 ml of potassium mercuric iodide and 50 ml of 0.5 N sodium hydroxide. Methanol was added to make the contents up to 250 ml. The mixture was shaken and a 25 ml aliquot was titrated with 0.5 N sulfuric acid, using phenolphthalein as an indicator.

Test substance : The test material was methylacetylene (also known as propyne). Purity of

the material is unknown.

Reliability : (2) valid with restrictions
Only one concentration was tested. The study is not as rigorous as a

guideline study.

11.09.2003 (15)

Type : Sub-chronic Species : Dog Sex : male/female

Strain :

Route of admin. : Inhalation Exposure period : 6 hours per day

Frequency of treatm. : 5 days/week for 6 months

Post exposure period

Doses : 28,700 ppm

Control group : yes, concurrent no treatment

NOAEL : < 28700 ppm

 Method
 : other

 Year
 : 1957

 GLP
 : No

 Test substance
 : other TS

Remark: This is a supporting study for the SIDS endpoint

Result : Chamber concentration: The concentration of material in the atmosphere of control animals was 2000 ppm. This was subtracted from the concentration analyzed in the atmosphere of exposed animals (30,700 ppm), to obtain a

corrected exposure concentration of 28,700 ppm.

Signs of toxicity during exposure: On the first day of exposure, marked salivation, excitability and muscular fasciculations were noted within 7 minutes of exposure. After 13 minutes, the dogs exhibited ataxia and mydriasis. After 30 minutes, one dog was lying on the chamber floor, in an early plane of anesthesia. One dog did not eat following the first exposure. Throughout the remaining exposures, similar signs of toxicity were observed. In addition, within 15 minutes of exposure, dogs appeared to be intoxicated (similar to alcohol). The dogs were excited and walked about the chamber, occasionally staggering and falling on the floor or against the

sides. Shortly after termination of exposure, the dogs would lie quietly on the chamber floor.

Tonic convulsions occurred in at least one of the dogs on days 22, 110, 123 and 137. There was a prodromal syndrome consisting of 15-30 minutes of hyperexcitability, which term inated in a tonic convulsion of a few minutes' duration. Dogs recovered soon after the episodes.

Exposed dogs lost weight during the first 6 weeks of the experiment, attained their initial weight by week 14, and continued to gain weight until termination.

There was no effect of treatment on any hematological, urine or biochemical index of toxicity. The gross appearance of all organs (specific organs examined were not listed) and microscopic examinations of the lung, liver, kidney, heart, spleen and GI tract in exposed animals were normal.

: Animals: Two dogs (one male and one female) weighing 7.6 and 9.0 kg, respectively, were exposed to an average concentration of 28,700 ppm methylacetylene for 6 hours/day, 5 days/week for 6 months. Two male dogs were housed in the same laboratory to serve as controls. The laboratory temperature was 25 +/- 1 degrees C.

Exposure: Exposures were performed in 500 liter, stainless steel chambers with a water-sealed lid. The inlet was equipped with a suitable device to inject methylacetylene vapor, and the outlet was equipped with an orifice flowmeter, control valve and exhaust pump. Methylacetylene vapor was injected into the inlet at a fixed rate of flow from a large steel cylinder. A constant rate of flow was maintained during exposure with a reducing pressure valve and an orifice flowmeter which was connected to a water manometer. The flow was constantly monitored. Methylacetylene was mixed with room air, which was drawn into the exposure chamber.

Test conduct: Animals were observed for signs of toxicity during and after exposure (specific times were not listed). Animals were observed at least daily for mortality. Animals were weighed on days 0, 13, 24, 31, 38, 45, 60, 64, 71, 76, 85, 95, 102, 109, 120, 127, 137, 141, 146, 158, 165, 173, 179 and at termination (date was not stated).

Blood samples were taken for analysis of sedimentation rate, hematocrit, hemoglobin and white blood cell count at approximately 10-day intervals. Biochemistries consisting of icterus index, blood urea nitrogen, blood sugar, plasma chloride, and plasma carbon dioxide combining power and urinalyses (appearance, reaction, specific gravity, protein, sugar, occult blood and microscopic examination) were also performed at approximately 10-day intervals. Sulfobromophthalein sodium (BSP) tests were done at various intervals by administering a dose of 5.0 mg/kg to each dog and drawing blood samples 15 and 30 minutes later. The percent retention of BSP was determined by comparing the values to those of standards. Blood volumes were determined by injecting 1 ml of Evans blue dye and drawing blood 10 minutes later.

Gross pathologies of animals that died were performed as soon as possible after death. Gross pathologies of animals that survived the course of treatment were performed upon termination. Sections of lung, liver, kidney, heart, spleen and GI tract were examined microscopically.

Concentration of Test Material: The concentration of material in the chamber was determined by drawing a known volume of the chamber atmosphere (measured with a wet-test meter) through 6 bubblers (in series) containing methanol. Samples were not drawn until the chamber concentration had equilibrated. The concentration of test material in each

Test condition

ld 74-86-2 5. Toxicity Date 21.10.2003

> bubbler was determined separately. If an appreciable mount of material was found in the last bubbler, the samples were drawn at a slower rate. Blank samples from chambers containing control animals were run to determine the contribution of animal metabolites.

Solution from each bubbler was placed into a 250 ml volumetric flask. containing 50 ml of potassium mercuric iodide and 50 ml of 0.5 N sodium hydroxide. Methanol was added to make the contents up to 250 ml. The mixture was shaken and a 25 ml aliquot was titrated with 0.5 N sulfuric

acid, using phenolphthalein as an indicator.

Test substance The test material was methylacetylene (also known as propyne). Purity of

the material is unknown.

(2) valid with restrictions Reliability

Only one concentration was tested in 2 dogs. The study is not as rigorous

as a guideline study.

11.09.2003 (15)

GENETIC TOXICITY 'IN VITRO'

Type Ames test

System of testing Salmonella typhimurium TA97, TA98, TA100

Test concentration up to 31 micrograms/plate

Cytotoxic concentr.

Result

Metabolic activation with and without

Result Negative Method Other 1984 Year GLP no data

Test substance as prescribed by 1.1 - 1.4

Remark : The test conditions used in the study were previously determined in a

> preliminary study that examined the 1) toxicity and mutagenicity of styrene oxide with log- and stationary-phase cells of TA100 with pre-incubation or plate incorporation, 2) mutagenicity testing of methylene chloride with the plate incorporation and preincubation techniques, 3) the effect of headspace volume and different types of shaking (during preincubation) on the mutagenic potential of styrene oxide and methylene chloride. 4) the effect of solvents and metabolic activation on the mutagenic potential of vaporphase mutagens, and 5) the effect of preincubation time (10 - 60 min) on the mutagenic potential of styrene oxide. The results indicated that the optimal system used preincubation (10-30 minutes) with log-phase cells in

full vials that were not shaken during preincubation.

The concentrations used were lower than that recommended in guideline tests (5000 micrograms/plate) due to limited solubility in the solvent.

There was no effect of acetylene on the number of mutants in the absence of S-9. The average number of mutants in control strains TA97, TA98 and TA100 without S-9 were 142, 25.7 and 184.7, respectively. The average

number of mutants in treated strains TA97, TA98 and TA100 without S-9 ranged from 97 - 106.3, 17.3 - 27.7 and 145.3 - 227.0, respectively.

There was no effect of acetylene on the number of mutants in the presence of rat S-9. The average numbers of mutants in control strains TA97, TA98 and TA100 with rat S-9 were 167.3, 34.3 and 174.0, respectively. The average number of mutants in treated strains TA97, TA98 and TA100 with rat S-9 ranged from 131.3-144.7, 23.3-34.7 and 119.0-157.7,

respectively.

There was no effect of acetylene on the number of mutants in the presence of hamster S-9. The average numbers of mutants in control strains TA97,

22/31

TA98 and TA100 with hamster S-9 were 184.0, 38.3 and 199.7, respectively. The average number of mutants in treated strains TA97, TA98 and TA100 with hamster S-9 ranged from 121.7- 149.7, 23.3 - 36.0 and 144.7 - 167.7, respectively.

The test was valid, since both concentrations of each positive control induced at least a two-fold increase in the number of mutants with respect to solvent controls.

Test condition

: Salmonella typhimurium strains TA97, TA98 and TA100 were obtained from Dr. Bruce Ames, University of California, Berkeley. Stationary cells were grown overnight (16 hours) with shaking at 50 rpm; log-phase cells were grown on the day of the experiment by inoculating a fresh nutrient broth culture with fresh overnight culture (1:10 dilution) and shaking the culture for 4 hours at 50 rpm and 37 +/- 0.5 degrees C. Plates were incubated for 48 hours, and colonies were counted with a calibrated automatic cell counter.

Rat and hamster liver S9 were derived from male Sprague-Dawley rats and male Syrian Golden hamster, respectively. Both rats and hamsters were induced with 500 mg/kg Aroclor 1254 five days before liver harvest.

Positive controls were as follows: 50 and 100 micrograms/plate 9-aminoacridine for TA97 without S-9, 1 and 2 micrograms/plate 2-nitrofluorene for TA98 without S-9, 1 and 2 micrograms/plate sodium azide for TA100 without S-9, 1 and 2 micrograms/plate 2-aminoanthracene for all strains with rat S-9, and 0.5 and 1 micrograms/plate for all strains with hamster S-9.

Test vials contained (per plate): 500 microliters of medium or 5% S9 mix. 100 microliters of bacteria (cell number was not indicated), 100 microliters of acetylene (0.3, 1, 3, 10, or 31 micrograms/plate) in acetone solvent, acetone alone (negative control) or positive control, and 600 microliters of overlay agar. Test concentrations were chosen based on the results of a preliminary toxicity and solubility studies. Each vial contained the contents for 3 plates (without headspace). Vials were preincubated for 10 min at 37 degrees C in sealed one-dram glass vials in a temperature-controlled exposure chamber that completely surrounded the glass vial. The vial was not shaken during preincubation. Toxicity was determined by plating approximately 1,000 colonies on histidine-supplemented agar. A viability index was calculated by comparing the number of colonies present on a dosed plate to a solvent control plate. A viability index below 50% indicated excessive toxicity. A positive response was defined as at least a two-fold increase in the number of mutants in treated cells vs. solvent controls at two increasing dose levels.

Aliquots of each sample used in the Ames test were removed (times were not stated) and assayed for acetylene concentration by GC analysis [6' chromosorb 102 packed 1/4" glass GC column (at 100 degrees C) with FI detection]. Each sample was assayed in triplicate, and mean concentration was calculated from the standard curve. Standards of test material were prepared by filling an evacuated 0.5 I gas bulb with acetylene and allowing the pressure to equilibrate to 1 atm. Samples were withdrawn through a septum in the bulb with a gas-tight syringe and chromatographed as described above. Duplicate injections were made for each point and a response curve of a least 3 points was established.

Test substance

: Purity of the test material was not given; however it was mentioned that the material was obtained from Matheson Gas Company and was of the highest quality available.

Reliability

: (2) valid with restrictions

Only three strains were used in the study.

Flag 16.10.2003

: Critical study for SIDS endpoint

(16)

Type : Bacterial reverse mutation assay

System of testing : S. typhimurium TA98, TA100, TA1535 and TA1537 and E. coli WP2uvrA

Test concentration : 0, 5, 10, 21 and 50%

Cytotoxic concentr. : no data

Metabolic activation: with and without

Result

Method: otherYear: 1994GLP: no dataTest substance: other TS

Remark

Fifteen different gases were tested in the study. Some of the materials caused dose-dependent increases in revertants in the absence and presence of S9, and others did not. Results obtained in the study were similar to those reported by others, which validated the model. It is unknown why the results at 5 and 10 % in the absence of S9 were not considered to be positive, since the number of mutants appears to be at least twice that of the control. However, it is difficult to determine the exact number since the results were depicted graphically, with tic marks on the x axis (number of revertants) placed at 50.

Result

Methyl acetylene did not cause an increase in mutations in any strain of Salmonella at any concentration in the absence or presence of S9 mix. Methylacetylene caused a dose dependent increase in the number of mutations in E. coli WP2 uvra in the absence or presence of S9 mix. The authors stated that the effect was positive at concentrations > = 21% without S9 mix (approximately > = 100 revertants/plate were detected) and > = 5% with S9 mix (approximately > = 75 revertants/plate were detected). The number of revertants in the controls with and without S9 mix was < 25/plate.

Test condition

Bacteria: S. typhimurium TA98, TA100, TA1535 and TA1537 were supplied by Dr. Bruce Ames, University of California, Berkeley and E. coli WP2 uvrA was supplied by Dr. M Ishizawa, Kyushu University, Fukuoka Japan. Stock cultures were stored at -80 degrees C. Bacteria were subcultured for 10 hours in nutrient broth before use.

S9 and S9 mix: Liver homogenate (S9) was prepared from male Sprague Dawley rats (6 weeks old). Phenobarbital and 5,6-benzoflavone were used as inducers. The S9 mix contained 4 mM NADPH, 4 mM NADH, 5 mM glucose 6-phosphate, 8 mM MgCl2, 33 mM KCl, 100 mMsodium phosphate buffer (pH 7.4) and 10-40% S9.

Exposure system: Gas from the cylinder was collected into a 20-liter gas sampling bag. Another 20-liter gas sampling bag was filled with dilution gas (HEPA-filtered air). A fixed volume of the test gas was pumped out from the gas sampling bag and pumped into another gas sampling bag (gas dilution bag), which had been filled with a fixed amount of the dilution gas using a flowmeter and pump. The gas dilution bag was squeezed by hand to mix the gases. The concentrations used in the test were calculated using the volumes of test and dilution gases.

Test material concentration: The concentration of gas in the bag was measured at the beginning of exposure using gas chromatography with FID/TCD detection. One ml of sample was withdrawn through the septum of the bag using a gas-tight syringe. Separations were performed using a Polapak Q column (3 mm x 2 m) or Silicone DC 550 column (3 mm x 2 m). Column temperature, injection temperature, and gas flow (N or He) were 70 degrees C, 120 degrees C and 50 ml/min, respectively. Concentrations used in the test were 0 (control), 5, 10, 21 and 50%.

5. Toxicity

ld 74-86-2 **Date** 21.10.2003

Mutation test: Bacterial plates were prepared using the spread method and the agar overlay method. For the spread method, 0.2 ml of a 0.5 mM histidine/biotin (for S. typhimurium) or 0.2 ml of a 0.5 mM L-tryptophan (for E coli) solutions were poured into sterile tubes, to which 0.5 ml of a 0.1 M phosphate buffer or S9 mix was added. Test bacteria (.1 ml) were added and the entire solution was spread onto a minimal glucose agar plate. For the agar overlay method, 0.5 ml of a 0.1 M phosphate buffer or S9 mix were mixed with 0.1 ml of bacteria. Immediately after adding 1 or 2 ml of top agar containing 0.1 micromoles of L-histidine/D-biotin or L-tryptophan, the mixture was poured onto minimal glucose agar plates. Based on the results of a preliminary study with 1,3-butadiene (see below), it is assumed that the agar overlay method was used to test methyl acetylene.

Prepared plates were placed upside down (without lids) in a plate holder and the plate holder was placed in a 10-liter gas sampling bag through a hole cut with scissors. The hole was sealed by folding the opening 2 or 3 times and securing the fold with adhesive tape. The air in the bag was removed with a pump to check that the bag was air-tight. A flow meter and pump were connected to the gas dilution bag and approximately 1 liter of the test gas (at a known concentration) was pumped into the gas exposure bag. The gas in the exposure bag was then sucked out with a pump and the remaining air in the exposure bag was washed out. After washing out the air, the gas exposure bag was filled with the test gas at a fixed amount per plate. The plates were kept at 25 or 37 degrees C (exact temperature was not listed) for a "fixed period". It is assumed that exposure time was 14 hours based on the preliminary study with 1,3-butadiene (see below). After exposure was terminated, the gas in the exposure bag was removed, HEPA-filtered air was pumped into the exposure bag and the plates were removed. The plates were placed in a hood for 30 minutes to allow the test material to evaporate and lids were placed on them. The plates were then incubated inverted for 24 hours at 37 degrees C.

The conditions listed above were chosen based on the results of a preliminary study with 1,3 butadiene, in which the effect of the volume of gas per plate (357, 625, 1250, 2500 or 5000 ml/plate, which corresponded to 14, 8, 4, 2 or 1 plates/bag), the amount of S9 (50, 100, 200 or 400 microliters/plate), the exposure temperature (30 or 37 degrees C), exposure period (2, 4, 14, 24 or 48 hours), and amount of top agar (0, 1, or 2 ml/plate) were examined. For each experiment, one factor was changed at a time. 1,3 butadiene was not mutagenic if the exposure period was < 4 hours and was optimally mutagenic after 14 hours of exposure. The rate of mutagenicity was lower if bags contained 1-4 plates. A concentration of 100 microliters/plate S9 was optimal. Exposure temperature did not have a significant effect. The agar overlay method was more sensitive than the spread method. The conditions used for the gases optimized the chances for a positive result while conserving resources.

Test substance

The test material was propyne (CAS No. 74-99-7, methyl acetylene), used as supplied by Tokyo Kasei Co. Ltd.

Reliability

 (2) valid with restrictions
 Criteria for a positive or negative test were not given. Purity of the test material is unknown.

16.10.2003 (1)

5.6 GENETIC TOXICITY 'IN VIVO'

5.7 CARCINOGENICITY

5.8.1	TOXICITY TO FERTILITY
F 0 0	DELICI ODBACA ITALI TOVICITY/ITED ATOCICALICITY
5.8.2	DEVELOPMENTAL TOXICITY/TERATOGENICITY
5.8.3	TOXICITY TO REPRODUCTION, OTHER STUDIES
5.9	SPECIFIC INVESTIGATIONS
5.10	EXPOSURE EXPERIENCE
5.10	LAT COUNT FULL HOL

ld 74-86-2 **Date** 21.10.2003

5. Toxicity

5.11 ADDITIONAL REMARKS

6. Analyt. Meth. for Detection and Identification

- 6.1 ANALYTICAL METHODS
- 6.2 DETECTION AND IDENTIFICATION

7. Eff. Against Target Org. and Intended Uses

7.1	FUNCTION
7.2	EFFECTS ON ORGANISMS TO BE CONTROLLED
7.3	ORGANISMS TO BE PROTECTED
7.4	USER
7.5	RESISTANCE

8. Meas. Nec. to Prot. Man, Animals, Environment

8.1	METHODS HANDLING AND STORING
8.2	FIRE GUIDANCE
8.3	EMERGENCY MEASURES
8.4	POSSIB, OF RENDERING SUBST, HARMLESS
-	
8.5	WASTE MANAGEMENT
0.10	
8.6	SIDE-EFFECTS DETECTION
0.0	GDE ET EGIO DETEGNON
8.7	SUBSTANCE REGISTERED AS DANGEROUS FOR GROUND WATER
0.7	SUBSTANCE REGISTERED AS DANGEROUS FOR GROUND WATER
88	REACTIVITY TOWARDS CONTAINER MATERIAL
XX	REALTIVITY TOWARDS CONTAINER WATERIAL

9. References ld 74-86-2
Date 21.10.2003

(1)	Araki A, Noguchi T, Kato F and Matsushima T. 1994. Improved method for mutagenicity testing of gaseous compounds by using a gas sampling bag. Mut Res 307: 335-344.
(2)	Atkinson R; Journal of Physical And Chemical Reference Data. Monograph No 1 (1989).
(3)	Daubert, T.E., R.P. Danner. Physical and Thermodynamic Properties of Pure Chemicals Data Compilation. Washington, D.C.: Taylor and Francis, 1989.
(4)	Davidson BM. 1925. Studies of intoxication. II. The action of acetylene. J Pharm Exper Ther 25: 119-135.
(5)	EPIWIN AOP Program (v1.90).
(6)	EPIWIN BIOWIN (v4.00)
(7)	EPIWIN Ecosar Program (v0.99) for neutral organic.
(8)	EPIWIN Fugacity Model Level III
(9)	EPIWIN Hydrowin Program (v1.67).
(10)	Fire Protection Guide to Hazardous Materials. 12 ed. Quincy, MA: National Fire Protection Association, 1997.,p. 325-11.
(11)	Franken H and Miklos L. 1933. Zentralb Gynaekol 42: 2493 - 2498, abstract cited in a literature search conducted by the Haskell Laboratory, on June 18, 1999.
(12)	Grayson M (Ed.). Kirk-Othmer Encyclopedia of Chemical Technology, 3 rd Ed., New York, John Wiley and Sons, 1978.
(13)	Hansch, C., Leo, A., D. Hoekman. Exploring QSAR - Hydrophobic, Electronic, and Steric Constants. Washington, DC: American Chemical Society., 1995.
(14)	Heymans C and Bouckaert JJ. 1925. CR Social Biol (Paris) 93:1036 - 1037, as described in ACGIH, 1991, Documentation of TLVs and BEIs (6th Ed).
(15)	Horn HJ, Weir RJ Jr and Reese WH. 1957. Inhalation toxicology of methylacetylene. Arch Ind Health 15: 20-26.
(16)	Hughes TJ, Sparacino C and Frazier S. 1984. Validation of chemical and biological techniques for evaluation of vapors in ambient air/mutagenicity testing of twelve (12) vaporphase compounds. EPA Report Number 68-02-3170, NTIS Publication PB84-164219.
(17)	Lide, D.R. (ed.). CRC Handbook of Chemistry and Physics. 73rd Ed. Boca Raton, FL: CRC Press Inc., 1992-1993., p. 3-26.
(18)	OHM/TADS. Oil and Hazardous Materials/Technical Assistance Data System search for Acetylene. Accessed on 2/18/2003.
(19)	Riggs LK. 1925. The physiologic properties of some unsaturated hydrocarbons. Proc Soc Exp Biol Med 22: 269-270.
(20)	Sax, N.I. Dangerous Properties of Industrial Materials. 6 th Ed. New York, NY: Van Nostrand Reinhold, 1984. 107.
(21)	Yalkowsky SH, Dannenfelser RM; The Aquasol database of Aqueous Solubility. Fifth ed, Tucson, AZ: Univ Az, College of Pharmacy (1992), as cited in the Hazardous Substances Data Bank.

10. Summary and Evaluation

ld 74-86-2 **Date** 21.10.2003

10.1	FND	POIN'	T SU	MMAF	RΥ

10.2 HAZARD SUMMARY

10.3 RISK ASSESSMENT